

Rudd Prod. #	Product	% Solids by Weight	Viscosity Zahn #2 - Secs.	Sag Resistance - Mills	Dry to Sand - Minutes	Block Free - Hours	VOC grams/liter	Lbs. HAPs/Lbs. Solids	Shelf Life - Months	Non-Yellowing
--------------	---------	--------------------	---------------------------	------------------------	-----------------------	--------------------	-----------------	-----------------------	---------------------	---------------

### Water Base Sanding Sealers

280115	NuWave™ CLEAR Water Base Sanding Sealer	34.4%	26	4	25	n/a	227	0.0107	12	Yes
		Fast dry. Easy to sand. Very low odor. Exceptional adhesion. High solids. Ultra-Low/No HAP.								
280119	NuWave™ OPAQUE Water Base Sanding Sealer - White	50.5%	77 KU	5	25	n/a	211	0.0023	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Fast dry. Easy to sand. Very low odor. Exceptional adhesion. Excellent stain blocking properties. High solids. Ultra-Low/No HAP.								
280187	Universal Hi-Build™ Water Base OPAQUE Undercoater	54.8%	70 KU	7	30	n/a	76	0.000	12	Yes
		Max tint: 4 fl. oz. of colorant per gallon of coating. Compatible with most water base and solvent base topcoats. Easy to sand. Very low odor. Exceptional adhesion. Tannin blocking properties. Ultra-Low/No HAP.								
280188	Universal Hi-Build™ Water Base Undercoater Neutral Base	58.5%	70 KU	6	40	n/a	78	0.000	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Compatible with most water base and solvent base topcoats. Easy to sand. Very low odor. Exceptional adhesion. Tannin blocking properties. Ultra-Low/No HAP.								

### Water Base Finishes

280103	NuWave™ CLEAR Water Base Lacquer	29.7-33.3%	25-30	5	45	18	262	0.0055	12	Yes
		Fast dry. Easy sand. Exceptional adhesion. Very low odor. High solids. Ultra-Low/No HAP.								
280190	NuWave™ OPAQUE Water Base Lacquer - White	38.2-53.0%	80 KU	7	50	24	154	0.0030	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Fast dry. Exceptional adhesion. High solids. Excellent vertical hang. Ultra-Low/No HAP.								
280180	NuWave™ OPAQUE Water Base Lacquer Deep Base	30.9-33.3%	35-40	4	35	24	260	0.0050	12	
		Max tint: 8 fl. oz. of colorant per gallon of coating. Fast dry. Exceptional adhesion. High solids. Achieve deep tone colors. Excellent hide. Ultra-Low/No HAP.								

### Exterior Water Base Finish

280183	ProWave™ Exterior Water Base CLEAR Varnish	40.7-41.8%	42	5	45	24	91.7	< 0.00	12	Yes
		Ideal for exterior doors and trim with moderate, indirect exposure. Excellent flexibility. Exceptional moisture resistance. High solids. Self-seal. UV absorbers. Ultra-Low/No HAP.								