

Water Base Finishes

Rudd Prod. #	Product	% Solids by Weight	Viscosity Zahn #2 - Secs.	Sag Resistance - Mils	Dry to Sand - Minutes	Block Free - Hours	VOC grams/liter	Lbs. HAPs/Lbs. Solids	Shelf Life - Months	Non-Yellowing
Water Base Sanding Sealers										
280187	Universal Hi-Build™ Water Base Opaque Undercoater - White	54.8%	70 KU	7	35	n/a	77	0.000	12	Yes
		Max tint: 4 fl. oz. of colorant per gallon of coating. Compatible with most water base and solvent base top-coats. Easy to sand. Very low odor. Exceptional adhesion. Tannin blocking properties. Ultra-Low/No HAP.								
280188	Universal Hi-Build™ Water Base Opaque Undercoater Neutral Base	58.5%	70 KU	6	40	n/a	78	0.000	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Compatible with most water base and solvent base top-coats. Easy to sand. Very low odor. Exceptional adhesion. Tannin blocking properties. Ultra-Low/No HAP.								
280189	Universal Hi-Build™ Water Base Clear Undercoater	40.7%	67 KU	5-6	45	n/a	98	0.001	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Can be used under clear NuWave Waterbase Lacquer as a clear sanding sealer. Compatible with most water base and solvent base topcoats. Easy to sand. Very low odor. Exceptional adhesion. Tannin blocking properties. Ultra-Low HAP.								
Water Base Finishes										
280103	NuWave™ Water Base Clear Lacquer	29.7-33.3%	25-30	5	45	18	262	0.0055	12	Yes
		Fast dry. Easy sand. Exceptional adhesion. Very low odor. High solids. Ultra-Low/No HAP.								
280190	NuWave™ Water Base Opaque Lacquer - White	38.2-53.0%	80 KU	7	50	24	154	0.0030	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Fast dry. Exceptional adhesion. High solids. Excellent vertical hang. Ultra-Low/No HAP.								
280180	NuWave™ Water Base Opaque Lacquer Deep Base	30.9-33.3%	35-40	4	35	24	260	0.0050	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Fast dry. Exceptional adhesion. High solids. Achieve deep tone colors. Excellent hide. Ultra-Low/No HAP.								
280250	DuraWave™ Water Base Opaque 1K/2K Polyurethane - White	37.6-40.04%	84 KU	5	60	6	272	0.026	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Can be catalyzed for superior chemical resistance. Isocya-nate/Aziridine-Free catalyst. Fast dry. High solids. Excellent vertical hang. Super-Low HAP.								
280300	DuraWave™ Water Base Clear 1K/2K Polyurethane	31.4-33.2%	84 KU	5	55	6	233	0.037	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Can be catalyzed for superior chemical resistance. Isocya-nate/Aziridine-Free catalyst. Fast dry. High solids. Excellent vertical hang. Super-Low HAP.								
Exterior Water Base Finish										
280183	ProWave™ Exterior Water Base Clear	39.7-41.8%	35*	5	45	24	91.7	< 0.00	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Ideal for exterior doors and trim with moderate, indirect exposure. Excellent flexibility. Exceptional moisture resistance. High solids. Self-seal. UV absorbers. Ultra-Low/No HAP. * #4 Ford cup								
280186	ProWave™ Exterior Water Base Opaque	45.8-47.2%	65 KU	5	45	24	78	< 0.00	12	Yes
		Max tint: 8 fl. oz. of colorant per gallon of coating. Ideal for exterior doors and trim with moderate, indirect exposure. Excellent flexibility. Exceptional moisture resistance. High solids. Self-seal. Ultra-Low/No HAP.								